

LREC9710HF-TX /RX

PCIe x4 Gigabit Fiber Uni-directional Server Adapter (Intel I350AM2 Based)

Description

LREC9710HF-TX/RX fiber network card is the second generation simplex communication gigabit fiber optic Ethernet Adapter, based on Intel I350AM2, researched and developed by Shenzhen Lianrui Electronics Co., LTD.

Transmit network card and receive network card compose the Ethernet Adapter, connecting by Single Core LC fiber patch cord.

Using the latest optical fiber simplex communication technology, effectively guarantee the stability of data transmission, reduce the packet loss rate. Since the simplex communication characteristics of light, this Ethernet Adapter not only achieve physical separation between the internal computer network and the external network, but also ensure that the data between internal and external networks in real time, reliable, secure simplex communication. With third-party software, LREC9710HF-TX/RX server adapter can be widely used in public security, government systems, military and other security departments as well as used in other confidential computer network.

Flexible I/O Virtualization

The LREC9710HF-TX/RX includes Intel® Virtualization Technology for connectivity (Intel® VT-c) to deliver I/O virtualization and Quality of Service (QoS) features designed directly into the controller on the adapter. I/O virtualization advances network connectivity models used in today's servers to more efficient models by providing Flexible Port Partitioning (FPP), multiple Rx/Tx queues, and on- controller QoS functionality that can be used in both virtual and non-virtual server deployments.

Scalable iSCSI Performance

An LREC9710HF-TX/RX with native iSCSI initiators built into Microsoft* Windows*, Linux*, and VMware* ESX platforms provides a simple, dependable, cost-effective way to connect to iSCSI SANs. These native initiators are broadly tested using multiple generations of operating systems, storage systems, and OS tools to help ensure reliability and ease of use. Standardizing on Intel® Ethernet Adapters for iSCSI enables administrators to use a single initiator, TCP/IP stack, and a common set of management tools and IT policies. In addition, Intel® Ethernet Server Adapters include a number of hardware features designed to accelerate iSCSI traffic and enhance data processing. For example, TCP segmentation offload and checksum offload capabilities help reduce processor usage, increase throughput, and deliver exceptional iSCSI performance. Finally, using native OS initiators, an LREC9710HF-TX/RX supports the CRC-32 digest instruction set included with Intel® Xeon® processor products, which improves transmission reliability and delivers an enterprise-class iSCSI solution.

Power Management Technologies

Today, companies everywhere are looking for ways to decrease energy consumption across the enterprise to



reduce costs and environmental impact, while at the same time solving increasingly important power density challenges. That's why Intel has introduced new, advanced Power Management Technologies (PMTs) with the LREC9710HF-TX/RX that enable enterprises to configure power options on the adapter and more effectively manage their power consumption.

Energy Efficient Ethernet (EEE)

The LREC9710HF-TX/RX supports the IEEE802.3az Energy Efficient Ethernet (EEE) standard so that, during periods of low network activity, EEE reduces the power consumption of an Ethernet connection by negotiating with a compliant EEE switch port to transition to a low power idle (LPI) state. This reduces the controller power to approximately 50% of its normal operating power, saving power on the network port and the switch port. As soon as increased network traffic is detected, the controller and the switch quickly come back to full power to handle the increased network traffic. EEE is supported for both 1000BASE-T and 100BASE-TX.

DMA Coalescing

Another power management technology that can reduce power on the server platform is DMA Coalescing (DMAC). Typically, when a packet arrives at a server, DMA calls are made to transfer the packet within the server. These calls wake up the processor, memory and other system components from a lower power state in order to perform the tasks required to handle the incoming packet. Based on the configurable DMAC settings, incoming packets are buffered momentarily before any DMA calls are made. This enables the controller to intelligently identify opportunities to batch multiple packets together so that when components are wakened from lower power states they can efficiently handle the batched packets at the same time. This enables platform components to remain in lower power states longer, which can dramatically reduce platform energy consumption. DMAC synchronizes DMA calls across all controller ports to ensure maximum power savings.

Software Tools and Management

Intel® Advanced Network Services (Intel® ANS) include new teaming technologies and techniques such as Virtual Machine Load-Balancing (VMLB) for Hyper-V environments. Today, Intel ANS includes a variety of teaming configurations for up to eight adapters, support for mixed vendors server adapters teaming and includes support for 802.1q VLANs, making Intel ANS one of the most capable and comprehensive tools for supporting server adapter teaming.

Additionally, Intel® PROSet for Windows* Device Manager and PROset CL extends driver functionality to provide additional reliability and Quality of Service features and configuration.

Features

General

Intel® Ethernet Controller I350
With PCI Express* V2.1 (5 GT/s) Support
Low-Profile and Standard height full
Use Single Core LC Fiber patch cord

Ethernet Features

IEEE* 802.3 auto-negotiation
1Gb/s Ethernet IEEE 802.3, 802.3u, 802.3ab PHY specifications Compliant
Integrated PHY for 10/100/1000 Mb/s for multispeed, full, and half-duplex
IEEE 802.3x and 802.3z compliant flow control support with software-controllable Rx thresholds and Tx pause frames
Automatic cross-over detection function (MDI/MDI-X)
IEEE 1588 protocol and 802.1AS implementation

Power Management and Efficiency

< 1W S0-Max (state) 1000BASE-T Active 90oC (mode)
< 400mW S0-Typ (state) 100BASE-T Active (mode)
IEEE802.3az - Energy Efficient Ethernet (EEE)
DMA Coalescing
Smart Power Down (SPD) at S0 no link / Sx no link
Active State Power Management (ASPM) Support
LAN disable function
Full wake up support
Advanced Power Management (APM) Support (formerly Wake on LAN)
Advanced Configuration and Power Interface (ACPI) specification v2.0c
Magic Packet* wake-up enable with unique MAC address
ACPI register set and power down functionality supporting D0 and D3 states
MAC Power Management controls
Low Power Link Up - Link Speed Control
Power Management Protocol Offload (Proxying)
Latency Tolerance Reporting (LTR)

I/O Virtualization Features

Eight transmit (Tx) and receive (Rx) queue pairs per port
Flexible Port Partitioning;
32 Virtual Functions on Quad-port or 16 Virtual Functions on Dual-port
Support for PCI-SIG SR-IOV specification
Rx/Tx Round-Robin Scheduling
Traffic Isolation
Traffic Steering
VM to VM Packet forwarding (Packet Loopback)
MAC and VLAN anti-spoofing
Malicious driver detection
Storm control
Per-pool statistics, offloads, and jumbo frames support
Independent Function Level Reset (FLR) for Physical and Virtual

Functions

IEEE 802.1q Virtual Local Area Network (VLAN) support with VLAN tag insertion, stripping and packet filtering for up to 4096 VLAN tags
IEEE 802.1q advanced packet filtering
Mirroring rules
Support for Simple VEPA
VF Promiscuous modes

Stateless Offloads/Performance Features

TCP/UDP, IPv4 checksum offloads (Rx/ Tx/Large-send); Extended Tx descriptors for more offload capabilities
IPv6 support for IP/TCP and IP/UDP receive checksum offload
Tx TCP segmentation offload (IPv4, IPv6)
Transmit Segmentation Offloading (TSO)
Interrupt throttling control
Legacy and Message Signal Interrupt (MSI) Modes
Message Signal Interrupt Extension (MSI-X)
Intelligent interrupt generation
Receive Side Scaling (RSS) for Windows environment
Scalable I/O for Linux environments (IPv4, IPv6, TCP/UDP)
Support for packets up to 9.5K Bytes (Jumbo Frames)
Low Latency Interrupts
Header/packet data split in receive
PCIe v2.1 TLP Processing Hint Requester
Descriptor ring management hardware for Transmit and Receive

Remote Boot Options

Preboot eXecution Environment (PXE) flash interface support
Intel® Ethernet iSCSI Remote Boot for Windows, Linux, and VMware
Intel Boot Agent software:
Linux boot via PXE or BOOTP, Windows* Deployment Services, or UEFI

Manageability Features

Management Component Transport Protocol (MCTP)
Firmware Based Thermal Management
IEEE 802.3 MII Management Interface
MAC/PHY Control and Status
Watchdog timer
Extended error reporting
Controller Memory Protection
Vital Product Data (VPD) Support

Adapter Product Features

Plug and play specification support
Intel® I/O Acceleration Technology (Intel® I/OAT)
Ships with full-height bracket installed; low-profile bracket included in package

Technical Features

Data rate supported per port: 1 000 Mbps
Bus type: PCI Express* 2.1 (5 GT/s)
Bus width: 4-lane PCI Express; operable in x4, x8 and x16 slots
Interrupt levels: INTA, INTB, INTC, INTD, MSI, MSI-X
Controller-processor: Intel Ethernet Controller I350
Power consumption (typical): 6.0 W
Storage temperature: -40 °C to 70 °C (-40 °F to 158 °F)
Operating temperature: 0 °C to 55 °C (32 °F to 131 °F)
Storage humidity: 90% non-condensing relative humidity at 35 °C

Network Operating Systems (NOS) Software Support

DOS, Novell ODI

Windows XP 32-bit (64-bit)

Windows Server 2003 32-bit (64-bit)

Windows Vista 32-bit (64-bit)

Windows 7 32-bit (64-bit)

Windows 8 32-bit (64-bit)

Windows 8.1 32-bit (64-bit)

Windows Server 2008 32-bit (64-bit)

Windows Server 2008 R2 32-bit (64-bit)

Windows Server 2012

Windows Server 2012 R2

Linux 2.4 series kernel, 2.6.x, 3.x

FreeBSD 7.x and most of the FreeBSD

UnixWare / Open Unix 8

Sun Solaris x86

VMware

Xen4

Ordering Information

M/N	Description	Remark:
LREC9710HF-TX	PCIe x4 1G Fiber Uni-directional Server Adapter (Transmit port)	with the RX matching use,1310nm,20km
LREC9710HF-RX	PCIe x4 1G Fiber Uni-directional Server Adapter (Receive port)	with the TX matching use,1310nm,20km

PS: Above details are only for reference, if there is any change, no inform will have.

COMPANION PRODUCTS

Fiber NIC

- LR-LINK PCI 100FX Desktop Adapter
- LR-LINK PCIe 100FX Desktop Adapter
- LR-LINK PCI 1000BASE-SX/LX Desktop Adapter
- LR-LINK PCIe 1000BASE-SX/LX Desktop Adapter
- LR-LINK PCIe 1000BASE-SX/LX Server Adapter
- LR-LINK PCIe 10GBASE-SR/LR Server Adapter
- LR-LINK PCIe 40GBASE-SR/LR Server Adapter

Copper NIC

- LR-LINK PCI 10/100Mbps Desktop Adapter
- LR-LINK PCIe 10/100Mbps Desktop Adapter
- LR-LINK PCI 10/100/1000Mbps Desktop Adapter
- LR-LINK PCIe 10/100/1000Mbps Desktop Adapter
- LR-LINK PCIe 10/100/1000Mbps Server Adapter
- LR-LINK PCIe 100/1Gbps/10Gbps Server Adapter

DOWNLOAD DRIVERS

To get the drivers, please visit us at <http://www.lr-link.com/ProductDriver/index1.shtml>

PRODUCT QUICK GUIDE

To know the network card basic knowledge to choose the suitable NIC you need, please visit us at: <http://www.lr-link.com/product.html>

CUSTOMER SUPPORT

LR-LINK customer Support Services offers a broad selection of programs including phone support and warranty service. For more information, contact us at Service and availability. <http://www.lr-link.com/service.shtml>

LianRui Electronic Co.LTD

A professional supplier of high-quality NIC:PCI,PCI-X,PCI-Express;SC,ST,LC,SFP,SFP+;100M,1G,10G,40G;single,dual,quad ports. all series fiber and copper NIC with nearly 150 specifications which can meet demands of various applications, continuously creates value for customers and partners as well as OEM/ODM services provided.

DECLARATION

Shenzhen Lianrui Electronics Co., Ltd is an efficient Ethernet adapter design company with independent research and development, using Intel,Broadcom, Mellanox, Marvell, VIA, Realtek and other manufacturers Ethernet controller, developed by our company's independent R & D design team,manufactured by our company workshop, and then sell.

Our products specifications come from modifying the chip manufacturer's specifications released. Product features, technical parameters, technology right, intellectual property rights and brand names etc.mentioned in specifications are just referenced only. There is no infringement meaning.If there is any important and sensitive content related, please contact our Lianrui company, we'll delete them, thank you.

SHENZHEN LIANRUI ELECTRONICS CO.,LTD

ADD:C4 Bldg., Xintang Industry Zone, Baishixia Fuyong Town, Bao'an District Shenzhen China 518103

Tel:86-755-33671531 Fax: 86-755-29082065

Product sales: lrlink@lr-link.com

Technical Support: support@lr-link.com

OEM & ODM service: info@lr-link.com

WEB: www.lr-link.com

LR-LINK[®]
Link your world to everywhere